

Recommended P.C.B. Layout

SPECIFICATION

- Current:1.0A Max.
- Voltage:30V Max.
- Withstanding Voltage:100V AC
- Contact Resistance:50 Milliohms Max.
- Insulation Resistance:100 Megaohms Min.
- Temperature Range:-55°C~+85°C
- Mating Force:35N Max.
- Withdrawal Force:7N Min.
- Durability:5000 Cycles Min.
- ⚠ Insulator:LCP+30%G.F.(UL94V-0),Black
- Contact:Phosphor Bronze
- ⚠ Shell:Phosphor Bronze,Nickel Plated
- RoHS Compliant

SUNROM.COM
 Part# 5692
<https://www.sunrom.com/m/5692>

DRAWING No.

5692

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

CYP

SCALE

NONE


REV.

A3

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

.X ±0.38 .X* ±2.0°
 .XX ±0.25 .XX* ±1.0°
 .XXX ±0.13 .XXX* ±0.5°

UNIT
 mm



NO.	REV.	REVISIONS	CHK	DATE
3	A3	Modify Data	HZF	07/04/2017
2	A2	Modify Data	HZF	03/11/2015
1	A1	Modify Data	HZF	05/09/2013
0	A0	NEW RELEASE	HZF	01/29/2010