



 <b>ALPHA &amp; OMEGA</b> SEMICONDUCTOR	<b>AO3415</b> <i>20V P-Channel MOSFET</i>																																	
<b>General Description</b> <p>The AO3415 uses advanced trench technology to provide excellent <math>R_{DS(ON)}</math>, low gate charge and operation with gate voltages as low as 1.8V. This device is suitable for use as a load switch applications.</p>	<b>Product Summary</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">V<sub>DS</sub></td><td style="width: 50%;">-20V</td></tr> <tr> <td>I<sub>D</sub> (at V<sub>GS</sub>=-4.5V)</td><td>-4A</td></tr> <tr> <td>R<sub>DS(ON)</sub> (at V<sub>GS</sub>= -4.5V)</td><td>&lt; 41mΩ</td></tr> <tr> <td>R<sub>DS(ON)</sub> (at V<sub>GS</sub>= -2.5V)</td><td>&lt; 53mΩ</td></tr> <tr> <td>R<sub>DS(ON)</sub> (at V<sub>GS</sub>= -1.8V)</td><td>&lt; 65mΩ</td></tr> </table> <p>ESD protected</p>	V <sub>DS</sub>	-20V	I <sub>D</sub> (at V <sub>GS</sub> =-4.5V)	-4A	R <sub>DS(ON)</sub> (at V <sub>GS</sub> = -4.5V)	< 41mΩ	R <sub>DS(ON)</sub> (at V <sub>GS</sub> = -2.5V)	< 53mΩ	R <sub>DS(ON)</sub> (at V <sub>GS</sub> = -1.8V)	< 65mΩ																							
V <sub>DS</sub>	-20V																																	
I <sub>D</sub> (at V <sub>GS</sub> =-4.5V)	-4A																																	
R <sub>DS(ON)</sub> (at V <sub>GS</sub> = -4.5V)	< 41mΩ																																	
R <sub>DS(ON)</sub> (at V <sub>GS</sub> = -2.5V)	< 53mΩ																																	
R <sub>DS(ON)</sub> (at V <sub>GS</sub> = -1.8V)	< 65mΩ																																	
																																		
 																																		
<b>Absolute Maximum Ratings</b> T <sub>A</sub> =25°C unless otherwise noted																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Parameter</th><th>Symbol</th><th>Maximum</th><th>Units</th></tr> </thead> <tbody> <tr> <td>Drain-Source Voltage</td><td>V<sub>DS</sub></td><td>-20</td><td>V</td></tr> <tr> <td>Gate-Source Voltage</td><td>V<sub>GS</sub></td><td>±8</td><td>V</td></tr> <tr> <td>Continuous Drain Current</td><td>I<sub>D</sub></td><td>-4</td><td rowspan="2" style="vertical-align: middle;">A</td></tr> <tr> <td>T<sub>A</sub>=70°C</td><td>I<sub>D</sub></td><td>-3.5</td></tr> <tr> <td>Pulsed Drain Current <sup>C</sup></td><td>I<sub>DM</sub></td><td>-30</td><td rowspan="3" style="vertical-align: middle;">W</td></tr> <tr> <td>T<sub>A</sub>=25°C</td><td>P<sub>D</sub></td><td>1.5</td></tr> <tr> <td>T<sub>A</sub>=70°C</td><td>P<sub>D</sub></td><td>1</td></tr> <tr> <td>Junction and Storage Temperature Range</td><td>T<sub>J</sub>, T<sub>STG</sub></td><td>-55 to 150</td><td>°C</td></tr> </tbody> </table>		Parameter	Symbol	Maximum	Units	Drain-Source Voltage	V <sub>DS</sub>	-20	V	Gate-Source Voltage	V <sub>GS</sub>	±8	V	Continuous Drain Current	I <sub>D</sub>	-4	A	T <sub>A</sub> =70°C	I <sub>D</sub>	-3.5	Pulsed Drain Current <sup>C</sup>	I <sub>DM</sub>	-30	W	T <sub>A</sub> =25°C	P <sub>D</sub>	1.5	T <sub>A</sub> =70°C	P <sub>D</sub>	1	Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to 150	°C
Parameter	Symbol	Maximum	Units																															
Drain-Source Voltage	V <sub>DS</sub>	-20	V																															
Gate-Source Voltage	V <sub>GS</sub>	±8	V																															
Continuous Drain Current	I <sub>D</sub>	-4	A																															
T <sub>A</sub> =70°C	I <sub>D</sub>	-3.5																																
Pulsed Drain Current <sup>C</sup>	I <sub>DM</sub>	-30	W																															
T <sub>A</sub> =25°C	P <sub>D</sub>	1.5																																
T <sub>A</sub> =70°C	P <sub>D</sub>	1																																
Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to 150	°C																															
<b>Thermal Characteristics</b>																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Parameter</th><th>Symbol</th><th>Typ</th><th>Max</th><th>Units</th></tr> </thead> <tbody> <tr> <td>Maximum Junction-to-Ambient <sup>A</sup> t ≤ 10s</td><td>R<sub>θJA</sub></td><td>65</td><td>80</td><td>°C/W</td></tr> <tr> <td>Maximum Junction-to-Ambient <sup>A,D</sup> Steady-State</td><td>R<sub>θJA</sub></td><td>85</td><td>100</td><td>°C/W</td></tr> <tr> <td>Maximum Junction-to-Lead</td><td>R<sub>θJL</sub></td><td>43</td><td>52</td><td>°C/W</td></tr> </tbody> </table>		Parameter	Symbol	Typ	Max	Units	Maximum Junction-to-Ambient <sup>A</sup> t ≤ 10s	R <sub>θJA</sub>	65	80	°C/W	Maximum Junction-to-Ambient <sup>A,D</sup> Steady-State	R <sub>θJA</sub>	85	100	°C/W	Maximum Junction-to-Lead	R <sub>θJL</sub>	43	52	°C/W													
Parameter	Symbol	Typ	Max	Units																														
Maximum Junction-to-Ambient <sup>A</sup> t ≤ 10s	R <sub>θJA</sub>	65	80	°C/W																														
Maximum Junction-to-Ambient <sup>A,D</sup> Steady-State	R <sub>θJA</sub>	85	100	°C/W																														
Maximum Junction-to-Lead	R <sub>θJL</sub>	43	52	°C/W																														

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=-250\mu\text{A}$ , $V_{GS}=0\text{V}$	-20			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=-20\text{V}$ , $V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$		-1	-5	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}$ , $V_{GS}=\pm 8\text{V}$			$\pm 10$	$\mu\text{A}$
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$ , $I_D=-250\mu\text{A}$	-0.3	-0.57	-0.9	V
$I_{D(\text{ON})}$	On state drain current	$V_{GS}=-4.5\text{V}$ , $V_{DS}=-5\text{V}$	-30			A
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=-4.5\text{V}$ , $I_D=-4\text{A}$ $T_J=125^\circ\text{C}$		34	41	$\text{m}\Omega$
		$V_{GS}=-2.5\text{V}$ , $I_D=-4\text{A}$		49	59	$\text{m}\Omega$
		$V_{GS}=-1.8\text{V}$ , $I_D=-2\text{A}$		52	65	$\text{m}\Omega$
		$V_{GS}=-1.5\text{V}$ , $I_D=-1\text{A}$		61		$\text{m}\Omega$
$g_{FS}$	Forward Transconductance	$V_{DS}=-5\text{V}$ , $I_D=-4\text{A}$		20		S
$V_{SD}$	Diode Forward Voltage	$I_S=-1\text{A}$ , $V_{GS}=0\text{V}$		-0.64	-1	V
$I_S$	Maximum Body-Diode Continuous Current				-2	A
<b>DYNAMIC PARAMETERS</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0\text{V}$ , $V_{DS}=-10\text{V}$ , $f=1\text{MHz}$	600	751	905	pF
$C_{oss}$	Output Capacitance		80	115	150	pF
$C_{rss}$	Reverse Transfer Capacitance		48	80	115	pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}$ , $V_{DS}=0\text{V}$ , $f=1\text{MHz}$	6	13	20	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g$	Total Gate Charge	$V_{GS}=-4.5\text{V}$ , $V_{DS}=-10\text{V}$ , $I_D=-4\text{A}$	7.4	9.3	11	nC
$Q_{gs}$	Gate Source Charge		0.8	1	1.2	nC
$Q_{gd}$	Gate Drain Charge		1.3	2.2	3.1	nC
$t_{D(\text{on})}$	Turn-On DelayTime	$V_{GS}=-4.5\text{V}$ , $V_{DS}=-10\text{V}$ , $R_L=2.5\Omega$ , $R_{\text{GEN}}=3\Omega$		13		ns
$t_r$	Turn-On Rise Time			9		ns
$t_{D(\text{off})}$	Turn-Off DelayTime			19		ns
$t_f$	Turn-Off Fall Time			29		ns
$t_{rr}$	Body Diode Reverse Recovery Time	$I_F=-4\text{A}$ , $dI/dt=500\text{A}/\mu\text{s}$	20	26	32	ns
$Q_{rr}$	Body Diode Reverse Recovery Charge	$I_F=-4\text{A}$ , $dI/dt=500\text{A}/\mu\text{s}$	40	51	62	nC

A. The value of  $R_{\text{JJA}}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{ C}$ . The value in any given application depends on the user's specific board design.

B. The power dissipation  $P_D$  is based on  $T_{J(\text{MAX})}=150^\circ\text{ C}$ , using  $\leq 10\text{s}$  junction-to-ambient thermal resistance.

C. Repetitive rating, pulse width limited by junction temperature  $T_{J(\text{MAX})}=150^\circ\text{ C}$ . Ratings are based on low frequency and duty cycles to keep initial  $T_J=25^\circ\text{ C}$ .

D. The  $R_{\text{JJA}}$  is the sum of the thermal impedance from junction to lead  $R_{\text{JUL}}$  and lead to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using  $<300\mu\text{s}$  pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-ambient thermal impedance which is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, assuming a maximum junction temperature of  $T_{J(\text{MAX})}=150^\circ\text{ C}$ . The SOA curve provides a single pulse rating.

COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)













Figure 6: Body-Diode Characteristics (Note E)

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

## Gate Charge Test Circuit &amp; Waveform



## Resistive Switching Test Circuit &amp; Waveforms



## Diode Recovery Test Circuit &amp; Waveforms

